

XIVI-IVI312

4G Mobile Wifi Hotspot



Product introduction:

The XM-M312 4G Mobile WiFi Hotspot XM-M312 is a new 4G pocket WiFi router. XM-M312 is a LTE Category 4 mobile hotspot which could support peak download speed to 150Mbps.

Key Feature

- able to connect with tablet pc, notebook and different types of wifi devices
- High speed to link, LTE download speed up to 150M
- friendly user interface
- maximum 3-4 hours working by battery 2100mah
- 10 Users connection support



Product Features:

Multi mode to work

First you need to put sim card, And charge it by usb cable. Also no need to connect usb cable cause it's have 2100mah battery .it will keep working till power offer. In this case, XM-M312 should be a good partner whenever you are at home or outside. It's easy to take and easy to use, worthy to have it.

Fast Connection

A secure download speed of 150 Mbps and a fast uploadspeed of 50 Mbps allowing you to stream or download videos and films in no time!

Travel

Travelling to a different country and have no access to Internet connection? Purchase a XM-M312 and you will have no problem connecting to the Internet abroad. All you need to do is buy a data sim card from the local area you will be staying in, connect, then there you go Internet access on holiday or from home.

Perfect for Small Businesses

XM-M312 allows you to you to share your Internet connection with up to 10 different Wi-Fi enabled devices. Perfect for cheap data roaming in your office. Giving you the best Internet experience at home and at work.



Hardware	
Model	XM-M312
MTK Chipset	MT6735
Wi-Fi Chipset	MT6625
Dimension (L \times W \times H) and Weight	98*61*15mm(0.15kg)
Storage	4GByte EMMC+512MByte DDR2
Frequency Band	A version :FDD band B1/B3/B5/B7/B8B20(Optional) TDD band:B38/B40/B41 WCDMA:B1/B5/B8
	B version:FDD band:B2/B4/B5/B12/B17 WCDMA:B2/B5
Wi-Fi	IEEE 802.11b/g/n
Transfer rate	3GPP Release9,Category 4,up to 150M DL and 50M bps UL@20MHz bandwidth
Encryption	Wi-Fi Protected Access™ (WPA/WPA2)2
LED Indicators	Battery Capacity, WIFI, Signal indicators
Internet	
Wi-Fi	Wi-Fi AP, Up to 10 users
WIFI SSID	4GMIFI_****



WIFI password	1234567890	
Interface		
Micro USB	1A Charge IN RNDIS	
SIM	Standard SIM Card (6PIN) *1 MICRO SIM*1, Dual SIM card Slot	
Micro SD	Up to 32GB (Or MICRO SIM)	
KEY	one Power button, one RESET key	
Operating Environment		
Operation system	PC Users: A PC with Windows XP (SP3), Windows Vista (SP1), Windows 7,or Windows 8 MAC Users: A Mac with OS X v10.5.7,OS X Lion v10.7.3 or later IPAD Uers: An iPhone, iPad, or iPod touch with iOS 5 or later Android Uers: An mobile Phone or Tablet PC with Android 2.3 or later	
Operation Browser	Internet Explorer 8.0 ,Mozilla Firefox 40.0 ,Google Chrome 40.0 ,Safari and above	
WEB		
Gateway	http://192.168.0.1	
Log in	User name: admin Password: admin Language(Chinese/English)	
Status	Connection; APN;IP; Signal Strength; Battery Capacity; Conneting time; Users	
Networks	APN confirguration: International roaming switch, APN, User name, Password, Authorization type modification, New APN, Restore defaulf APN parameters. Traffic statistics: Traffic Limitation: Afering reaching the set value, limit the speed as set.	
Wifi	WLAN configuration: SSID modifiation, encryption methods, encryption password, Maximum user number setting, support PBC-WPS	
System Management	Login password management: User name, password modification System operation: Restart, Shutdown, Restore factory setting System Information: Check software version, WLAN MAC address, IMEI NO. Phonebook setting: New, modify, look up, delete contact	
SMS Management	SMS open, delete, send	
Micro SD	WEB sharing	