

# ZK1060F

# **CAPWAP Protocol Intelligent Gateway and AC controller**



ZK1060F is a medium and large-scale enterprise use gateway based on CAPWAP protocol. Built-in Intel CPU, configured with up to 6 Gigabit WAN ports, with WAN port load balancing, multi-operator access, line backup, network overlay, policy routing and other multi-WAN features. At the same time, this product also supports intelligent flow control., network firewall, VPN settings, VLAN management, remote access control management and other functions, allowing 1000 end users to access and provide high-speed network, to maximize protectbu'zion against network storms, to ensure the normal operation of the entire network, is widely applied to large and medium-sized enterprises, villages, hotels, cafes, shopping malls and other places.

ZK1060F is also a very professional and intelligent AC control platform, which can be used as the main route in the network, or as a bypass AC, centrally manage and configure up to 500 thin APs, and can be remotely managed and maintained later. High performance, easy installation, easy maintenance, etc., greatly saving material and labor costs in the network layout.

Finally, the ZK1060F can be used as an authentication gateway to access the cloud platform to achieve advertising and WeChat authentication, WeChat with Wi-Fi authentication, user authentication, SMS authentication, and other authentication methods.

Even as a bypass AC controller, the ZK1050F can be connected to the cloud platform. Although in different cities and in different networks, administrators can monitor, manage and configure the main page of the ZK1060F at any time.



# **Main Features**

#### A. Multi-WAN and multi-WAN port load balancing

ZK1060F supports PPPoE/DHCP/static IP/access, can access up to 500 end users. Support multi-WAN, support multi-WAN port load balancing, line backup, network overlay and other functions to provide users with a more stable and faster network.

In addition.

## B. Online behavior control and intelligent flow control

Sometimes the public network bandwidth is plentiful, but users complain that the network speed is too slow. The ZK1050F solves this kind of problem well through the online behavior specification:

#### C. VLAN management

The ZK1060F supports VLAN management, which can trunk the VLAN ID of the VLAN switch, and then allows the AC controller to manage the wireless AP under the VLAN switch.

#### D. Cloud platform access and authentication

The ZK1060F supports cloud platform access in gateway mode and AC mode. Even if you are in a different city and are in different networks, the administrator can easily cut into the ZK1060F web page through the cloud platform for monitoring, modification, and maintenance. In addition, in the gateway mode, the ZK1060F supports multiple authentication methods, such as WeChat authentication, and SMS authentication, which make the entire network layout more professional and bring more advertising effects.

### **E:AP** management function

## Zero configuration and grouping

Add a zero configuration group before accessing wireless AP, and the wireless AP will automatically get the corresponding configuration from the group. No additional configuration is required, which is simple and convenient

Alternatively, you can add different groups throughout the network and send the configuration data to the corresponding wireless AP in the group

#### Built-in intelligent channel analyzer

The ZK1060F has a built-in intelligent channel analyzer to Support intelligent channel selection, select the best channel for wireless AP,, so that the wireless AP selects the channel with the least interference and achieves the most stable wireless coverage.

#### Automatically assign an IP address to the wireless AP

The ZK1060F has a built-in DHCP server that automatically assigns IP addresses to wireless APs, which avoids the possibility of IP address conflicts and saves manpower configuration costs.



Product characteristics		
Model	ZK1060F	
Standards and protocols	IEEE 802.3, 802.3u, 802.3ab TCP/IP, DHCP, ICMP, NAT, PPPoE, SNTP, HTTP, DDNS, IPsec, PPTP, L2TP CAPWAP Protocols	
CPU	Celeron 1037 chipset, Dual-core 1.8GHz	
RAM	4G DDR3 1333\1600MHz (Max 8GB)	
SSD	32G SSD	
Heat dissipation	Ultra-quiet ball-bearing fan	
Interface	1 * 10/100/1000 WAN, Up to 4 WAN ports	
	5 * 10/100/1000 LAN, Minimum 2 LAN ports	
Product characteristics		
Interface	1 * Console	
	2 * USB2.0 6*lan	
Power Supply	AC100`240V, Max 50W	
Size	440mm*285mm*44mm	
Weight	Volume 5KG, Actual 3KG	
Operating Temperature	-20℃~55℃	
Storage Temperature	-40°C ~ 70°C	
Humidity	5% ~ 97%RH (No condensation)	



Software functions		
AP management	Maximum management 500PCS wireless AP	
	Centralized and remote management, configure wireless AP	
	View user status	
WAN port connection	DHCP, Static IP, PPPoE,	
DHCP	DHCP Server/client	
MAC address cloning	Modify WAN/LAN/DMZ MAC address	
VLAN management	Manage wireless AP by dividing VLAN IDs	
Load balancing	Multi-WAN, multi-operator access	
	Intelligent load balancing	
Software functions		
Load balancing	Line backup	
	Speed superposition	
	Policy routing: based on source IP address, destination IP address, source mac address, network interface, domain name, destination port, external network interface, identity binding, etc.	
	Protocol binding	
	online test	
Routing function	Static route	



Routing function	Static route	
Behavior management	Completely block P2P software	
	P2P flow control and bandwidth allocation	
	File transfer and URL filtering	
	Full control of network behavior	
Bandwidth control	IP-based bandwidth control	
	Guarantee/limit bandwidth	
	Time strategy	
	IP-based session restrictions	
Security center	MAC address filtering URL/keyword filtering Web content filtering IP address filtering Port forwardingDMZ	
Defense center	TCP/UDP/ICMP flood defense; Block TCP scanning Block PING WAN port	
Software functions		
ARP detection	Send a GARP packet	
	ARP scanning of WAN/LAN port	
	IP-MAC binding	
Authentication	Local authenticationRemote authentication (WeChat authentication, WeChat with Wi-Fi authentication, SMS authentication, user authentication, GOOGLE authentication, etc.)	
Management	Web/CLI/Telnet management portal Remote Management Remote Management	